TECHNICAL SPECIFICATION

20m Rope & Grab

20m Rope & Grab / FAR0811

DESCRIPTION

Fall Arrest system with a 12mm diameter kernmantle rope anchorage line with an non-openable stainless steel rope grab equipped with energy absorber. The anchorage line has one connector, with the other side folded back and stitched 10cm.

OPTIONS

20m Rope & Grab (FAR0811)

SAFETY STANDARDS

EN 353-2

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Fall Indicator
No

Material
12mm Kernmantle Rope

Rope Ends
1 Side 1 Connector. Other Side Folded Back and Stitched 10cm

Adjustment Device
Non-Openable Stainless Steeel Rope Grab

Delivered With
2 Screwgate Connectors In Alloy Steel. Gate Opening 18mm. Conforms to EN362 Class B & M

Length
20m

Shock Absorber
External

Protective Rope Sleeve
No

Product Weight
3240g

DOWNLOADS

Image Pack (ZIP)
doc-far0810-far0811-far0812.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.